

XBO DHP for digital cinema projection

Lampes Xénon arc court




Domaines d'application

- Cinema projection

Caractéristiques produit

- Short arc with highest luminance for brighter screen illumination
- A lifetime of reliable performances with constant 6000 K color temperature
- Easy to maintain
- High level of arc stability
- Hot restart and instant light on screen
- Dimmable in a wide range



Fiche de données gamme de produits

Fiche technique

Description produit	Données électriques		Dimensions & poids			
	Puissance nominale	Courant de fonctionnement	Diamètre	Longueur	Longueur du culot hors pins	Longueur câbles/ conducteurs, au primaire
XBO 1200 W/DHP OFR	1200,00 W	41...63 A	46,5 mm	345,0 mm	295,00 mm	130 mm
XBO 1600 W/DHP OFR	1600,00 W	57...86 A	46,5 mm	345,0 mm	295,00 mm	130 mm
XBO 2000 W/DHP L OFR	2000,00 W	64...95 A	55,0 mm	345,0 mm	295,00 mm	130 mm
XBO 2200 W/DHP OFR	2200,00 W	68...95 A	52,0 mm	345,0 mm	295,00 mm	130 mm
XBO 2500 W/DHP OFR	2500,00 W	63...95 A	55,0 mm	345,0 mm	295,00 mm	130 mm
XBO 3000 W/DHS OFR	3000,00 W	77...113 A	60,0 mm	342,0 mm	302,00 mm	155 mm
XBO 3000 W/DHP OFR	3000,00 W	77...113 A	55,0 mm	345,0 mm	295,00 mm	130 mm
XBO 3000 W/DHP L OFR	3000,00 W	76...111 A	60,0 mm	345,0 mm	295,00 mm	130 mm
XBO 3000 W/DHP XL OFR	3000,00 W	76...111 A	60,0 mm	345,0 mm	295,00 mm	130 mm
XBO 4000 W/DHP L OFR	4000,00 W	95...137 A	60,0 mm	345,0 mm	295,00 mm	130 mm
XBO 4000 W/DHP LL OFR	4000,00 W	95...137 A	60,0 mm	345,0 mm	295,00 mm	130 mm
XBO 4000 W/DHP XL OFR	4000,00 W	95...137 A	60,0 mm	345,0 mm	295,00 mm	130 mm
XBO 4000 W/DHP OFR	4200,00 W	91...130 A	60,0 mm	345,0 mm	295,00 mm	130 mm
XBO 4500 W/DHP OFR	4500,00 W	108...155 A	60,0 mm	436,0 mm	393,00 mm	155 mm
XBO 4500 W/DHP L OFR	4500,00 W	108...155 A	60,0 mm	436,0 mm	393,00 mm	155 mm
XBO 6000 W/DHP OFR	6000,00 W	131...174 A	78,0 mm	436,0 mm	393,00 mm	155 mm
XBO 6000 W/DHP L OFR	6000,00 W	125...160 A	78,0 mm	436,0 mm	393,00 mm	155 mm
XBO 6000 W/DHP XL OFR	6000,00 W	125...160 A	78,0 mm	436,0 mm	393,00 mm	155 mm
XBO 6500 W/DHP OFR	6500,00 W	133...173 A	78,0 mm	436,0 mm	393,00 mm	155 mm
XBO 6500 W/DHP L OFR	6500,00 W	133...173 A	78,0 mm	436,0 mm	393,00 mm	155 mm
XBO 6500 W/DHP XL OFR	6500,00 W	133...173 A	78,0 mm	436,0 mm	393,00 mm	155 mm
XBO 6500 W/DHP IX OFR	6500,00 W	133...173 A	78,5 mm	436,0 mm	393,00 mm	155 mm

Fiche de données gamme de produits

Description produit	Données électriques		Dimensions & poids			
	Puissance nominale	Courant de fonctionnement	Diamètre	Longueur	Longueur du culot hors pins	Longueur câbles/ conducteurs, au primaire
XBO 7000W/DHP OFR	7000,00 W	130...175 A	78,0 mm	436,0 mm	393,00 mm	155 mm

Description produit	Longueur de câble	Ecartement des électrodes	Distance culot / foyer lumineux (LCL)	Poids du produit	Température
					Température max au point de pincement
XBO 1200 W/DHP OFR	130,0	3,5 mm	123,0 mm ¹⁾	485,00 g	230 °C
XBO 1600 W/DHP OFR	130,0	3,5 mm	123,0 mm ¹⁾	485,00 g	230 °C
XBO 2000 W/DHP L OFR	130,0	4,5 mm	123,0 mm ¹⁾	530,00 g	230 °C
XBO 2200 W/DHP OFR	130,0	3,7 mm	123,0 mm ¹⁾	534,00 g	230 °C
XBO 2500 W/DHP OFR	130,0	4,5 mm	123,0 mm ¹⁾	558,00 g	230 °C
XBO 3000 W/DHS OFR	155,0	6,0 mm	145,0 mm ¹⁾	591,00 g	230 °C
XBO 3000 W/DHP OFR	130,0	4,5 mm	123,0 mm ¹⁾	581,00 g	230 °C
XBO 3000 W/DHP L OFR	130,0	5,0 mm	123,0 mm ¹⁾	623,00 g	230 °C
XBO 3000 W/DHP XL OFR	130,0	5,0 mm	123,0 mm ¹⁾	623,00 g	230 °C
XBO 4000 W/DHP L OFR	130,0	6,0 mm	123,0 mm ¹⁾	645,00 g	230 °C
XBO 4000 W/DHP LL OFR	130,0	6.3 mm	123,0 mm	645,00 g	
XBO 4000 W/DHP XL OFR	130,0	6.3 mm	123,0 mm ¹⁾	645,00 g	230 °C
XBO 4000 W/DHP OFR	130,0	6,0 mm	123,0 mm ¹⁾	670,00 g	230 °C
XBO 4500 W/DHP OFR	155,0	6,0 mm	170,5 mm ¹⁾	853,00 g	230 °C
XBO 4500 W/DHP L OFR	155,0	6,0 mm	170,5 mm ¹⁾	853,00 g	230 °C
XBO 6000 W/DHP OFR	155,0	7,5 mm	170,5 mm ¹⁾	1000,00 g	230 °C
XBO 6000 W/DHP L OFR	155,0	7,5 mm	170,5 mm ¹⁾	1050,00 g	230 °C
XBO 6000 W/DHP XL OFR	155,0	8,0 mm	170,5 mm ¹⁾	1000,00 g	230 °C
XBO 6500 W/DHP OFR	155,0	7,5 mm	170,5 mm ¹⁾	1023,00 g	230 °C
XBO 6500 W/DHP L OFR	155,0	8,0 mm	170,5 mm ¹⁾	1023,00 g	230 °C
XBO 6500 W/DHP XL OFR	155,0	8,0 mm	170,5 mm ¹⁾	1023,00 g	230 °C
XBO 6500 W/DHP IX OFR	155,0	8.1 mm	170,5 mm ¹⁾	1000,00 g	230 °C
XBO 7000W/DHP OFR	155,0	7,5 mm	170,5 mm ¹⁾	1023,00 g	230 °C

Description produit	Durée de vie		Donnée produit supplémentaire	
	Durée de vie	Service Warranty Lifetime	Anode (désignation standard)	Cathode (désignation standard)
XBO 1200 W/DHP OFR	3000 h	3800 h	SFaX30-14	SFc30-16
XBO 1600 W/DHP OFR	3000 h	3800 h	SFaX30-14	SFc30-16
XBO 2000 W/DHP L OFR	3300 h	3500 h	SFaX30-14	SFc30-16
XBO 2200 W/DHP OFR	1500 h	2000 h	SFaX27-14x80	SFc27-16/55
XBO 2500 W/DHP OFR	1700 h	2000 h	SFaX27-14x80	SFc27-16/55
XBO 3000 W/DHS OFR	1500 h	2000 h	SFaX27-9.5	SFa27-7.9
XBO 3000 W/DHP OFR	1500 h	1900 h	SFaX27-14x80	SFc27-16/55
XBO 3000 W/DHP L OFR	1900 h	2100 h	SFaX27-14x80	SFc27-16/55

Fiche de données gamme de produits

Description produit	Durée de vie		Donnée produit supplémentaire	
	Durée de vie	Service Warranty Lifetime	Anode (désignation standard)	Cathode (désignation standard)
XBO 3000 W/DHP XL OFR	2200 h	2400 h	SFaX27-14x80	SFc27-16/55
XBO 4000 W/DHP L OFR	1300 h	1500 h	SFaX27-14x80	SFc27-16/55
XBO 4000 W/DHP LL OFR	1500 h	1900 h	SFaX27-14x80	SFc27-16/55
XBO 4000 W/DHP XL OFR	1900 h	2100 h	SFaX27-14x80	SFc27-16/55
XBO 4000 W/DHP OFR	1100 h	1400 h	SFaX27-14x80	SFc27-16/55
XBO 4500 W/DHP OFR	1000 h	1300 h	SFaX30-9.5	SFa30-7.9
XBO 4500 W/DHP L OFR	1300 h	1500 h	SFaX30-9.5	SFa30-7.9
XBO 6000 W/DHP OFR	650 h	800 h	SFaX30-9.5	SFa30-7.9
XBO 6000 W/DHP L OFR	900 h	1100 h	SFaX30-9.5	SFa30-7.9
XBO 6000 W/DHP XL OFR	1000 h	1200 h	SFaX30-9.5	SFa30-7.9
XBO 6500 W/DHP OFR	500 h	750 h	SFaX30-9.5	SFa30-7.9
XBO 6500 W/DHP L OFR	700 h	800 h	SFaX30-9.5	SFa30-7.9
XBO 6500 W/DHP XL OFR	900 h	1000 h	SFaX30-9.5	SFa30-7.9
XBO 6500 W/DHP IX OFR	1000 h	1200 h	SFa30-7.9	SFaX30-14
XBO 7000W/DHP OFR	400 h	500 h	SFaX30-9.5	SFa30-7.9

Description produit	Capacités		Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
	Refroidissement	Position de fonctionnement	Date of Declaration	Primary Article Identifier
XBO 1200 W/DHP OFR	Forcé	s 15 p 15 ²⁾	05-03-2024	4008321396433 4052899497962 4062172030472
XBO 1600 W/DHP OFR	Forcé	s 15 p 15 ²⁾	06-03-2024	4052899254831 4062172030465
XBO 2000 W/DHP L OFR	Forcé	s 15 p 15 ²⁾	06-03-2024	4052899275638 4062172030427
XBO 2200 W/DHP OFR	Forcé	s 15 p 15 ²⁾	06-03-2024	4008321865489 4062172030373
XBO 2500 W/DHP OFR	Forcé	s 15 p 15 ²⁾	06-03-2024	4008321821706 4052899010413 4062172030380
XBO 3000 W/DHS OFR	Forcé	s 15 p 15 ²⁾	05-03-2024	4008321199065 4008321330017 4062172030540
XBO 3000 W/DHP OFR	Forcé	s 15 p 15 ²⁾	05-03-2024	4008321309532 4008321330048 4008321865496 4052899091818 4052899096073 4052899195783 4052899287785 4052899468191 4062172030410
XBO 3000 W/DHP L OFR	Forcé	s 15 p 15 ²⁾	06-03-2024	4052899212886 4052899235908 4052899317277 4062172030502

Fiche de données gamme de produits

	Capacités		Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Description produit	Refroidissement	Position de fonctionnement	Date of Declaration	Primary Article Identifier
XBO 3000 W/DHP XL OFR	Forcé	s 15 p 15 ²⁾	07-03-2024	4062172092401
XBO 4000 W/DHP L OFR	Forcé	p15/s15 ²⁾	06-03-2024	4052899212879 4052899235915 4052899468214 4062172030403
XBO 4000 W/DHP LL OFR	Forcé	p15/s15 ²⁾	07-03-2024	4062172114080
XBO 4000 W/DHP XL OFR	Forcé	s 15 p 15 ²⁾	07-03-2024	4062172092395
XBO 4000 W/DHP OFR	Forcé	s 15 p 15 ²⁾	05-03-2024	4008321309686 4008321546272 4008321865526 4052899091825 4052899096080 4052899195790 4052899287792 4052899317208 10046135694810 4062172030397
XBO 4500 W/DHP OFR	Forcé	s 15 p 15 ²⁾	05-03-2024	4008321199072 4008321633422 4062172030571
XBO 4500 W/DHP L OFR	Forcé	s 15 p 15 ²⁾	06-03-2024	4052899343344 4062172030588
XBO 6000 W/DHP OFR	Forcé	s 15 p 15 ²⁾	05-03-2024	4008321549693 4052899144026 4062172030663
XBO 6000 W/DHP L OFR	Forcé	s 15 p 15 ²⁾	06-03-2024	4052899087088 4052899343405 4062172030670
XBO 6000 W/DHP XL OFR	Forcé	s 15 p 15 ²⁾	07-03-2024	4062172110839
XBO 6500 W/DHP OFR	Forcé	s 15 p 15 ²⁾	05-03-2024	4008321676078 4062172030731
XBO 6500 W/DHP L OFR	Forcé	s 15 p 15 ²⁾	06-03-2024	4052899448636 4062172030755
XBO 6500 W/DHP XL OFR	Forcé	s 15 p 15 ²⁾	06-03-2024	4052899593640 4062172031684
XBO 6500 W/DHP IX OFR	Forcé	h90 ²⁾	07-07-2023	4062172363792
XBO 7000W/DHP OFR	Forcé	s 15 p 15 ²⁾	06-03-2024	4062172031707

Description produit	Candidate List Substance 1	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
XBO 1200 W/DHP OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	f6cc71e9-adae-4c95- afe0-07d36b5e74f6

Fiche de données gamme de produits

Description produit	Candidate List Substance 1	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
XBO 1600 W/DHP OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	ddc0ca29-d545-4244-bd3d-01657e49e316
XBO 2000 W/DHP L OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	3cc8eb7d-934b-482f-ade0-0afdb83ac51b
XBO 2200 W/DHP OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	5e903ee1-3cc9-40f0-ae95-0a54da9c2b3a
XBO 2500 W/DHP OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	2699a8c3-f6d1-4519-a2c4-83464e509907
XBO 3000 W/DHS OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	0ad1e6ac-a107-4e86-a73c-0a8cdc49edb4 468df0c2-2da9-47b4-a001-357079e3d0c0
XBO 3000 W/DHP OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	A303E60B-72E8-4104-9C0C-1F16ADEED959 2C70619C-7452-40E1-9F11-72C36A77558D 34a49bce-cf7a-477b-8d7b-991718631ed4
XBO 3000 W/DHP L OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	42b5a623-65c3-4fc7-b272-e9973ba1c9ec
XBO 3000 W/DHP XL OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	4d1b0324-7408-4c16-afc9-0e4165c645a1

Fiche de données gamme de produits

Description produit	Candidate List Substance 1	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
XBO 4000 W/DHP L OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	a182c938-75ef-44e7-a0e6-e8e301002b19 ee6fe08d-465e-439d-9156-a1830163f87d
XBO 4000 W/DHP LL OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	68536058-a0f0-4f39-8967-a173bfd19c5b
XBO 4000 W/DHP XL OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	cc43340f-d501-48a4-97e6-2064cf408c27
XBO 4000 W/DHP OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	ce588d4a-f4ef-4dda-8e54-ddab4457e440 56ff5a8b-6ea4-41c2-bd17-d898f6c185d1
XBO 4500 W/DHP OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	012f940f-18dd-409c-9473-04140360c548
XBO 4500 W/DHP L OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	3de76945-7771-4e03-9280-550799b927c9
XBO 6000 W/DHP OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	8566eac2-b860-4860-9c27-f7b8e2871b1f
XBO 6000 W/DHP L OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	e1be3907-8f4f-4d48-b496-86874180bac4
XBO 6000 W/DHP XL OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	e98aa7da-cb44-4008-ab03-b605fac43791

Fiche de données gamme de produits

Description produit	Candidate List Substance 1	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
XBO 6500 W/DHP OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	412959b3-e26e-4a82-89ba-3ce9a6fa908b
XBO 6500 W/DHP L OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	326fc61e-87e5-491e-a54a-876602402f4a
XBO 6500 W/DHP XL OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	0afbcf5a-721a-4942-bd3d-6024b2eff6a3
XBO 6500 W/DHP IX OFR				In work
XBO 7000W/DHP OFR	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	885c4405-74b6-4820-817d-399a936e4918

1) Distance bas du culot / pointe de l'électrode (froid)
2) Pour une position verticale de fonctionnement : anode (+) au-dessus

Fiche de données gamme de produits

Consignes de sécurité

En raison de leur luminance élevée, des émissions d'UV et d'une pression interne élevée en fonctionnement comme à froid, les lampes XBO ne doivent fonctionner que dans des boîtiers de lampe fermés spécialement conçus à cet effet. Les lampes xénon sont hautement explosives. Lorsqu'elles sont chaudes, les lampes xénon peuvent provoquer des marques de brûlures. Elles ne doivent être manipulées que lorsqu'elles sont à température ambiante. Utiliser systématiquement les enveloppes de protection fournies lors de la manipulation de ces lampes. Lors de l'emballage des lampes et lors de leur installation et de leur retrait sans leur enveloppe de protection, portez toujours un équipement de protection (masque facial avec protection du cou, gilet de protection et gants anti-coupures non pelucheux). Pour plus d'informations veuillez consulter la notice spécifique fournie dans l'emballage et les instructions d'utilisation.

Conseil d'application

Pour plus d'informations sur les applications et les graphiques, veuillez vous référer à la fiche de données produit.

Avertissement

Sous réserve de modifications. Sauf erreur ou omission. Veuillez à toujours utiliser la version la plus récente.