

LINEARlight FLEX

Rubans flexibles de LED de couleur, sécables



Caractéristiques produit

- Peut être divisé jusqu'à la plus petite unité ou un multiple de celle-ci sans aucune incidence sur le fonctionnement du reste de la platine
- Gradable par impulsions (modulation de largeur d'impulsions)

Avantages produits

- Faible hauteur pour un montage encastré ou en saillie de faible profondeur
- Faible puissance thermique
- Montage flexible 3-D possible
- Platine flexible avec ruban adhésif à double face pour un montage simple
- LF05A avec des dimensions plus petites et des options de coupe supplémentaires grâce à l'utilisation du capot de fermeture LF-2TERM

Domaines d'application

- Injection de lumière dans les présentoirs et guides lumineux de faible profondeur
- Signalétique d'information, éclairage publicitaire ou éclairage de vitrines
- Rétroéclairage de contours complexes
- Pour des applications décoratives : LF05A
- Applications décoratives et petites voûtes

Fiche de données gamme de produits

Technique / Accessoires

- Connexion simplifiée avec CONNECTsystem en option

Conseil d'application

Pour plus d'informations sur les applications et les graphiques, veuillez vous référer à la fiche de données produit.

Support de vente et support technique

Support de vente et support technique www.osram.fr

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015. The contained light source is intended for use in applications requiring high-quality coloured light.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Avertissement

Sous réserve de modifications. Sauf erreur ou omission. Veuillez à toujours utiliser la version la plus récente.