

LF700RGBW -G1-865-06

LINEARlight Colormix Flex | Couleurs flexible – Modules LED avec changement de couleur



Caractéristiques produit

- Bande de LED flexible et sécable avec des LED RGB en ligne

Avantages produits

- Couleur changeante homogène
- Grande liberté de conception grâce à la flexibilité du module et à la possibilité de le découper
- Montage et connexion simples
- Montage facile sur de nombreuses surfaces lisses grâce à une bande autocollante située au dos

Domaines d'application

- Éclairage d'effets en architecture
- Injection de lumière dans les présentoirs et guides lumineux de faible profondeur
- Effets dynamiques dans les zones publiques



Fiche de données produit

Fiche technique

Données électriques

| | |
|---|---------------------|
| Type de courant | Courant direct (DC) |
| Accidental reverse input voltage protection up to | 25 V |
| Puissance nominale | 57,60 W |
| Tension nominale | 24,0 V |
| Intensité nominale | 2,4 A |
| Plage de tension | 23...25 V |

Données photométriques

| | |
|--------------------------------|------------|
| Flux lumineux par mètre | 697 lm |
| Efficacité lumineuse | 129 lm/W |
| Couleur de la LED | RGB, white |
| Total des flux lumineux utiles | 4182 lm |

Données photométriques

| | |
|----------------------|-------|
| Angle de rayonnement | 120 ° |
|----------------------|-------|

Information module de LED

| | |
|-----------------------------|----|
| Nombre de LED par composant | 12 |
|-----------------------------|----|

Dimensions & poids



| | |
|---------------------------|-----------|
| Longueur | 6000,0 mm |
| Longueur – composant seul | 150,0 mm |
| Largeur | 10,0 mm |
| Hauteur | 1,70 mm |
| Poids du produit | 116,00 g |

Fiche de données produit

Température

| | |
|----------------------------------|----------------------------|
| Plage de température au point Tc | -20...+85 °C ¹⁾ |
| Plage de température de stockage | -40...+85 °C |

¹⁾ Exceeding the maximum ratings will reduce expected life time or destroy the LED strip.

Donnée produit supplémentaire

| | |
|------------------------------|---------------|
| ID of contained light source | LS_TRV_285496 |
| Code EAN de remplacement | 4052899525344 |

Capacités

| | |
|----------|-----|
| Gradable | Oui |
|----------|-----|

Certificats & Normes

| | |
|---|----------------|
| Normes | CE/EAC/ENEC/UL |
| Energy efficiency class of the contained light source | F |

Données logistiques

| | |
|------------------------|--------------|
| Nomenclature douanière | 940540399000 |
|------------------------|--------------|




Technique / Accessoires

- Installation rapide avec le système optionnel SLIM TRACK
- Parfaitement adapté aux ballasts électroniques OPTOTRONIC 24 V















Texte de la feuille de

- not relevant
- not relevant
- not relevant
- Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.

Données de téléchargement

| Dossier | |
|---|--|
|  | User instruction LINEARlight Flex |
|  | Fiche technique produit LINEARlight Flex Colormix RGBW V2 |
|  | Brochures Light is freedom of design (EN) |

Fiche de données produit

| | |
|---|---|
|  | Déclaration de Conformité EAC Certificate |
|  | Déclaration de Conformité ENEC10_VDE Certificate |
|  | Déclaration de Conformité UL Certificate |
|  | Déclaration de Conformité CB TEST CERTIFICATE DE1-59711 |
|  | Déclarations de conformité Declaration of Conformity |
|  | Déclarations de conformité Manufacturers Declaration of Conformity |
|  | Eulumdat Eulumdat LF700RGBW-G1-865-06 |
|  | Eulumdat Eulumdat LF700RGBW-G1-8xx-06 Blue |
|  | Eulumdat Eulumdat LF700RGBW-G1-8xx-06 Green |
|  | Eulumdat Eulumdat LF700RGBW-G1-8xx-06 Red |
|  | IES data IES data LF700RGBW-G1-865-06 |
|  | IES data IES data LF700RGBW-G1-8xx-06 Blue |
|  | IES data IES data LF700RGBW-G1-8xx-06 Green |
|  | IES data IES data LF700RGBW-G1-8xx-06 Red |

Fiche de données produit

Ecodesign regulation information:

ul>This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015. The contained light source is intended for use in applications requiring high-quality coloured light.

Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.

In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer.

In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.

Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Données logistiques

| Code produit | Description produit | Unité d'emballage (Pièces/Unité) | Dimensions (longueur x largeur x hauteur) | Volume | Poids brut |
|---------------|----------------------|----------------------------------|---|----------------------|------------|
| 4062172166133 | LF700RGBW -G1-865-06 | Carton de regroupement 8 | 241 mm x 195 mm x 205 mm | 9.63 dm ³ | 2047.00 g |

Le code produit mentionné décrit la petite quantité d'unité qui peut être commandée. Une unité peut contenir un ou plusieurs produits. Lorsque vous passez la commande, merci de bien vouloir entrer une unité ou un multiple d'une unité.

Avertissement

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.