

# ULTRA LIFE H1

Longer life and 4 year guarantee



## 4 year OSRAM guarantee

For a worry-free driving pleasure. Refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee) for precise conditions

## Extra lifetime

Up to four times longer lifetime compared to standard halogen lamps

## More durability

For longer replacement cycles and additional reliability and comfort



## The durable light with up to four times longer lifetime

OSRAM ULTRA LIFE automotive lamps are a favorite when it comes to durability. They have an impressive lifespan up to four times longer compared to standard halogen lamps and last up to 100,000 km (with an average annual mileage of 14,259 km and 60% light on). OSRAM provides a 4 year guarantee for the reliable ULTRA LIFE headlight lamps ([www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)). In addition to this, ULTRA LIFE headlight lamps have a modern design with silver cap (H4/H7/H11). They are therefore ideal for frequent drivers or people who use daytime running lights, and can also be used in clear-glass headlights.

Technical data

Product information

|                                             |                        |
|---------------------------------------------|------------------------|
| Order reference                             | 64150ULT               |
| Application (Category and Product specific) | Halogen headlight lamp |

Electrical data


|                 |                    |
|-----------------|--------------------|
| Power input     | 68 W <sup>1)</sup> |
| Nominal voltage | 12.0 V             |
| Nominal wattage | 55.00 W            |
| Test voltage    | 13.2 V             |

<sup>1)</sup> Maximum

Photometrical data

|                         |         |
|-------------------------|---------|
| Luminous flux           | 1550 lm |
| Luminous flux tolerance | ±15 %   |
| Color temperature       | 3200 K  |

Dimensions & weight



|                |         |
|----------------|---------|
| Diameter       | 9 mm    |
| Product weight | 6.30 g  |
| Length         | 67.5 mm |

Lifespan

|             |        |
|-------------|--------|
| Lifespan B3 | 1200 h |
| Lifespan Tc | 2000 h |

Additional product data

|                             |        |
|-----------------------------|--------|
| Base (standard designation) | P14.5s |
|-----------------------------|--------|

Capabilities

|            |     |
|------------|-----|
| Technology | HAL |
|------------|-----|

Certificates & standards

|              |    |
|--------------|----|
| ECE category | H1 |
|--------------|----|

Country specific categorizations

|                 |          |
|-----------------|----------|
| Order reference | 64150ULT |
|-----------------|----------|


Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |                                                                                                                                                               |
|-----------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Date of Declaration                                                   | 05-03-2024                                                                                                                                                    |
| Primary Article Identifier                                            | 4008321416162   4008321416209   4008321416100   4052899412156   4052899412170   4052899987043   4062172257008   4052899425187   4062172388122   4062172395526 |
| Candidate List Substance 1                                            | No declarable substances contained                                                                                                                            |
| Declaration No. in SCIP database                                      | In work                                                                                                                                                       |

Country specific information

| Product code  | METEL code      | SEG-No. | STK-Number | UK Org |
|---------------|-----------------|---------|------------|--------|
| 4008321416162 | OSRA64150ULTDUO | -       | -          | -      |
| 4008321416162 | OSRA64150ULTDUO | -       | -          | -      |
| 4008321416209 | OSRA64150ULT    | -       | -          | -      |
| 4008321416216 | OSRA64150ULT    | -       | -          | -      |
| 4008321416209 | OSRA64150ULT    | -       | -          | -      |

Product datasheet



Others graphics

Logistical Data

| Product code  | Product description | Packaging unit<br>(Pieces/Unit) | Dimensions (length<br>x width x height) | Volume               | Gross weight |
|---------------|---------------------|---------------------------------|-----------------------------------------|----------------------|--------------|
| 4008321416100 | ULTRA LIFE H1       | Blister<br>1                    | 135 mm x 95 mm x<br>24 mm               | 0.31 dm <sup>3</sup> | 29.00 g      |
| 4008321416117 | ULTRA LIFE H1       | Shipping carton box<br>10       | 225 mm x 105 mm x<br>145 mm             | 3.43 dm <sup>3</sup> | 240.00 g     |
| 4008321416162 | ULTRA LIFE H1       | Hard Cover Box<br>2             | - x - x -                               |                      | 138.00 g     |
| 4062172059404 | ULTRA LIFE H1       | Shipping carton box<br>10       | 268 mm x 126 mm x<br>125 mm             | 4.22 dm <sup>3</sup> | 154.00 g     |
| 4008321416209 | ULTRA LIFE H1       | Folding carton box<br>1         | 25 mm x 23 mm x<br>70 mm                | 0.04 dm <sup>3</sup> | 9.00 g       |
| 4008321416216 | ULTRA LIFE H1       | Bundle<br>10                    | 113 mm x 50 mm x<br>70 mm               | 0.40 dm <sup>3</sup> | 90.00 g      |
| 4008321416223 | ULTRA LIFE H1       | Shipping carton box<br>100      | 122 mm x 109 mm x<br>361 mm             | 4.80 dm <sup>3</sup> | 995.00 g     |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

| File                                                                                |                                               |
|-------------------------------------------------------------------------------------|-----------------------------------------------|
|  | Brochures<br>724901_ULTRA LIFE Leaflet EN     |
|  | Product movie<br>724899_ULTRA LIFE Trailer EN |

|                                                                                   |                                            |
|-----------------------------------------------------------------------------------|--------------------------------------------|
|  | 360 Degree Image<br>ULTRA LIFE H1 64150ULT |
|-----------------------------------------------------------------------------------|--------------------------------------------|

References / Links

Guarantee terms are available at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



OSRAM