

Lok-it! Power Series (PS)



Areas of application

- Concert Lighting
- Club & Disco
- Stage & Theatre
- Studio, TV, & Film
- Architecture & Architainment

Product features and benefits

- Power Series (PS) lamps offer even more compact Lok-it! options with enhanced performance features
- Individual performance features are color-coded for easy identification and include BRILLIANT lamps with high CRI > 90 and BLUE lamps that offer 7500 K for bright white light
- Robust design with eXtreme Seal (XS) technology, allowing up to 450°C at the pinch seal
- Consistent lumen output over the life of the lamp
- Improved ceramic base allows high voltage up to 35kV
- Higher luminous efficacy than conventional HID lamps provides higher fixture efficiency
- Power series offers enhanced performance features and versatility, including BRILLIANT lamps with high CRI and BLUE lamps that offer 7500K for bright white light



June 24, 2025, 05:30:32 Lok-it! Power Series (PS)

Product family datasheet

Technical data

	Electrical Data	Electrical Data		Photometric Data	
Product description	Nominal wattage	Nominal voltage	Nominal luminous flux	Color temperature	
Lok-it! 1000/PS	1000 W	85 V	85000 lm	6000 K	
Lok-it! 1000/PS Blue	1000 W	85 V	75000 lm	7200 K	
Lok-it! 1000/PS Brilliant	1000 W	85 V	82000 lm	6000 K	
Lok-it! 1400/PS Brilliant	1400 W	95.5 V	118000 lm	6000 K	
Lok-it! 1700/PS	1700 W	84.5 V	135000 lm	6000 K	
Lok-it! 1800/PS Brilliant	1800 W	88 V	148000 lm	6000 K	
Lok-it! 2000/PS Brilliant	2000 W	108 V	165000 lm	6000 K	

	Lifetime Data	
Product description	Nominal lifetime	
Lok-it! 1000/PS	950 hr	
Lok-it! 1000/PS Blue	750 hr	
Lok-it! 1000/PS Brilliant	750 hr	
Lok-it! 1400/PS Brilliant	750 hr	
Lok-it! 1700/PS	750 hr	
Lok-it! 1800/PS Brilliant	750 hr	
Lok-it! 2000/PS Brilliant	750 hr	

Product family datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, Lok-it! lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.