

LFD800T -G2-930-06

LINEARlight FLEX Diffuse Top | – Modules LED pour des applications professionnelles et industrielles

Caractéristiques produit

- Long operational length per single power feed up to 10 m



Avantages produits

- IP66/IP68 protection with high performance silicone
- Reliable connection over long periods of time: IP66/67 connector with built-in protection against liquids penetrating through the wires into the LED strip

Domaines d'application

- Signalétique et enseignes lumineuses



Fiche de données produit

Fiche technique


Données électriques

Puissance nominale par mètre	13,5 W
------------------------------	--------

Données photométriques

Flux lumineux par mètre	870 lm
Ecart-type de correspondance de couleur	≤3 sdc _m
Ra Indice de rendu des couleurs	90

Dimensions & poids



Poids du produit	104000 g
Longueur	60000 mm
Largeur	141 mm
Hauteur	1080 mm

Donnée produit supplémentaire

ID of contained light source [AGGR]	LS_TRV_286453
-------------------------------------	---------------

Données logistiques

Nomenclature douanière	85395100000
------------------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	07-07-2023
Primary Article Identifier	4062172270533
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1

Fiche de données produit

Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	94d1bcd2-a482-4675-9264-ff4370221f7a

Texte de la feuille de

- not relevant
- not relevant
- not relevant
- Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.

Données de téléchargement

Dossier	
	User instruction LINEARlight FLEX DIFFUSE
	Fiche technique produit LINEARlight FLEX DIFFUSE Top_G2_Specification Sheet (EN)
	Brochures App Guide LINEARlight Flex Diffuse (EN)
	Brochures Light is freedom of design (EN)
	Déclaration de Conformité VDE ENEC CERTIFICATE 40052516 160823
	Déclaration de Conformité LINEARlight Flex DP UL 4413809 200622
	Eulumdat LFD800T-G2-930-10-ldt
	IES data LFD800T-G2-930-10-IES

Fiche de données produit

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Données logistiques

Code produit	Description produit	Unité d'emballage (Pièces/Unité)	Dimensions (longueur x largeur x hauteur)	Volume	Poids brut
4062172270533	LFD800T -G2-930-06	Carton de regroupement 6	420 mm x 246 mm x 430 mm	44.43 dm ³	11640.00 g

Le code produit mentionné décrit la petite quantité d'unité qui peut être commandée. Une unité peut contenir un ou plusieurs produits. Lorsque vous passez la commande, merci de bien vouloir entrer une unité ou un multiple d'une unité.

Avertissement

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.