

LINEARlight FLEX Protect POWER 800

Modules LED pour des applications professionnelles et industrielles



Caractéristiques produit

- Bande de LED flexible et sécable
- Flux lumineux : jusqu'à 800 lm/m
- Type de protection : IP67

Avantages produits

- Color uniformity better than 2 SDCM on the entire LED strip and between strips
- Flux lumineux élevé
- Grande liberté de design grâce à des dimensions compactes
- Silicone de haute qualité pour une très longue durée de vie et une grande flexibilité
- Connexion simple grâce aux connecteurs pré-montés
- Design extraordinaire et matériaux de haute qualité
- Montage facile sur de nombreuses surfaces lisses grâce à une bande autocollante située au dos

Domaines d'application

- Éclairage d'accentuation des façades
- Intégration dans plafond
- Intégration dans le mur
- Éclairage de voûtes
- Éclairage de machines
- Éclairage de chemins
- Pour une utilisation à l'extérieur

Fiche de données gamme de produits

Technique / Accessoires

- Raccordement simplifié grâce au système d'appariement optionnel CONNECTsystem
- Installation rapide avec le système optionnel SLIM TRACK
- Parfaitement adapté aux ballasts électroniques OPTOTRONIC 24 V

Conseil d'application

Pour plus d'informations sur les applications et les graphiques, veuillez vous référer à la fiche de données produit.

Texte de la feuille de

- not relevant
- not relevant
- not relevant
- Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.

Support de vente et support technique

Support de vente et support technique www.osram.fr

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Avertissement

Sous réserve de modifications. Sauf erreur ou omission. Veuillez à toujours utiliser la version la plus récente.