

# Fiche de données produit

## P R F CLAS A DIM 7 W/840 E27

PARATHOM Retrofit CLASSIC A DIM | Lampes LED gradables, forme classique



- Perfect for decorative installations Domestic applications  
General illumination Outdoor use in outdoor luminaires  
only (minimum IP65)

- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp Very low energy consumption Robust  
against vibrations No UV and near-IR radiation in the light beam Instant 100 % light, no warm-up time No UV and near-IR  
radiation in the light beam Can be easily fitted instead of ordinary light bulbs



## Fiche de données produit

### Fiche technique

#### Données électriques

Puissance nominale	7.00 W
Puissance nominale	7.00 W
Tension nominale	220...240 V
Fréquence de fonctionnement	50...60 Hz
Max. lamp no. on circuit break. 10 A (B)	80
Max. lamp no. on circuit break. 16 A (B)	120
Intensité nominale	0.044 A
Puissance équivalente à une lampe	60 W


#### Données photométriques

Flux lumineux nominale	806 lm
Flux lumineux	806 lm
Rated color temperature	4000 K
Ra Indice de rendu des couleurs	≥80
Teinte de couleur (désignation)	Cool White
Ecart-type de correspondance de couleur	≤6 sdcn
Temp. de couleur	4000 K
Flux lumineux	806 lm
Flux résiduel en fin de vie nomi [calc.]	0.70

#### Données photométriques

Angle de rayonnement	320.00 °
Temps d'amorçage	< 0.5 s

#### Dimensions & poids



Longueur totale	105.0 mm
-----------------	----------

## Fiche de données produit

Diamètre	60.0 mm
Forme de l'ébauche	A60
Poids du produit	32.00 g
Longueur	105.0 mm

### Température

Plage de température ambiante	-20...+40 °C
-------------------------------	--------------

### Durée de vie

Durée de vie nominale	15000 h
Durée de vie	15000 h
Nombre de cycles de commutation	100000
Maintien du flux lumineux en fin de vie	0.70

### Donnée produit supplémentaire

Culot (désignation standard)	E27
Teneur en mercure	0.0 mg
Sans mercure	Yes
Design / version	Frosted
Élimination appropriée cft DEEE	Oui
Code EAN de remplacement	4058075590830
Notes bas de page util. uniquem. produit	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value/LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance)
Code EAN de remplacement	4058075438958

### Capacités

Gradable	Yes
----------	-----

### Certificats & Normes

Classe d'énergie efficace	E
Consommation d'énergie	7 kWh/1000h

## Fiche de données produit

Type de protection	IP20
--------------------	------

### Classements spécifiques à chaque pays

Référence de commande	LEDPCLA60D 7W/8
-----------------------	-----------------

### Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4058075438958   4058075590830
Declaration No. in SCIP database	In work

### Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

### Données logistiques

Code produit	Description produit	Unité d'emballage (Pièces/Unité)	Dimensions (longueur x largeur x hauteur)	Volume	Poids brut
4058075590830	P RF CLAS A DIM 7 W/840 E27	Carton de regroupement 10 Pieces Etui carton fermé	315 mm x 131 mm x 126 mm	5.20 dm <sup>3</sup>	553.00 g

Le code produit mentionné décrit la petite quantité d'unité qui peut être commandée. Une unité peut contenir un ou plusieurs produits. Lorsque vous passez la commande, merci de bien vouloir entrer une unité ou un multiple d'une unité.

### Avertissement

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner  
of LEDVANCE of LAMPS

**OSRAM**

OSRAM GmbH  
Marcel-Breuer-Strasse 6  
80807 Munich, Germany