

# LEDDriving HL EASY H10

LED replacement for conventional fog lamps



**Cool White color temperature of 6,000 K**

Better visibility in foggy situations with a perfect color match for xenon and LED headlights. Signs, obstacles and hazards can be recognized sooner.



**Superior brightness**

More light allows to see farther and therefore react sooner with reduced glaring thanks to an optimized light distribution



**Ultra compact LED replacement for conventional H10 fog lamps as socket solution**

Easy installation with optimized compatibility



**New OSRAM LED fog lamps to increase safety and performance**

The latest generation of OSRAM LED fog lamps provides an even more convenient solution in order to replace and upgrade existing halogen fog lamps: With its ultra compact dimensions, the OSRAM LEDDriving FL provides optimized compatibility as well as easy plug & play installation. Upgrading with state-of-the-art LED technology and a color temperature of 6,000 K for a stylish cool white look as well as improved visibility. These LED products offer a perfect color match with xenon and LED headlights and are for conventional H10 fog lamps. A pair of new LEDDriving FL lamps, comes with a 3-year OSRAM guarantee as well as with a long service life by less energy consumption. For

precise guarantee conditions please refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee). Please note: These products are not ECE-approved and must not be used on public roads in any exterior application. Use on public roads will invalidate both the operating license and insurance coverage. Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

Product family datasheet

Technical data

Product description	Product information		General Product Information	Electrical Data	
	Product type (off-road vs. on-road)	Application (Category and Product specific)	Global order reference	Power input	Nominal voltage
LEDDriving FL $\triangleq$ H10	Off-road $\triangleq$ H10	Mainly used for fog light applications	9145DWESY	9.43 W	12 V

Product description	Nominal wattage	Test voltage	Photometric Data		Physical Attributes & Dimensions
			Nominal luminous flux	Luminous flux tolerance	Diameter
LEDDriving FL $\triangleq$ H10	8 W	13.5 V	720 lm	$\pm 15$ %	17.2 mm

Product description	Diameter	Lifetime Data		Capabilities	Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
		Lifespan B3	Lifespan Tc	Technology	Primary article identifier
LEDDriving FL $\triangleq$ H10	17.2 mm	2500 hr	5000 hr	LED	4052899605060   4062172401913   4062172033329

Product description	Candidate list substance 1	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDDriving FL $\triangleq$ H10	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	5bb0763b-d3d5-4ad4-9acb-80e77f971c23   b86477a2-9ace-40c3-a83c-07c2a8a5ba94   1d54fd7a-44a9-43a5-b0fd-acb4b3cbf3a7   df34dec2-e5d8-4f51-8a1c-a3c24fb12f06   5114875c-f327-4bd9-8308-3aa281a00817

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.Detailed guarantee terms can be found at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee).

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



061