

OPTOTRONIC FIT D NFC HC L

Linéaire / Courant constant – Non gradable



Domaines d'application

- Éclairage de serres
- Industry lighting
- Convient aux luminaires de classe de protection I

Avantages produits

- Global usage - CE & cURus approval
- Very high efficiency (up to 97%)
- Protection against 4 kV burst and 2 kV surge voltage (L-N and L-N/PE)

Caractéristiques produit

- Line frequency: 47.5...60 Hz
- Versatile scope of application due to output power range of up to 380 W
- Supply voltage: 220...240 V / 277 V / 400 V
- Disponible avec gamme de courants de sortie : jusqu'à 1 400 mA

Fiche de données gamme de produits

Conseil d'application

Pour plus d'informations sur les applications et les graphiques, veuillez vous référer à la fiche de données produit.

Support de vente et support technique

Support de vente et support technique www.osram.fr

Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Avertissement

Sous réserve de modifications. Sauf erreur ou omission. Veuillez à toujours utiliser la version la plus récente.