OSRAM

NIGHT BREAKER LED SMART ECE H11



The NIGHT BREAKER LED family - OSRAM's first ECE street-legal LED retrofit lamps



Approved for all 12V vehicle models 1)

Approved for all 12V vehicle models, in all ECE member states, for all light functions as a replacement for all H11 lamps and H11 bases



Up to 6 times longer lifetime 3)

Vibration resistant, environmentally friendly, and cost-efficient



Cool white & 6000K

Modern and intense white light with a color temperature similar to daylight



A revolutionary development in the retrofitting lamp sector. The new ECE street legal NIGHT BREAKER LED SMART ECE H11. OSRAMs first ECE homologated LED retrofit lamp.

OSRAMs new NIGHT BREAKER LED SMART ECE H11 is fully homologated according to ECE R37 and consequently approved for all 12V vehicles in all ECE member states for all light functions as suitable replacement for all H11 lamps and H11 bases.

The lamp's ECE R37 homologation eliminates the need for matching headlamp approval numbers, carrying official approval documents, or applying stickers.

They offer a modern and bright white light with a color temperature of up to 6000 Kelvin and impress with its extra brightness²⁾, while the glare of other road users falls below the permissible maximum values by up to 50%²⁾.

In comparison to standard lamps, such as halogen lamps, these LED retrofit lamps consume up to 60% less energy and convince thanks to LED technology and the specially developed vibration-resistant design, with up to 6 times longer life time²⁾. They have been tested in our DIN-certified environmental simulation laboratory for extreme external influences in terms of the ingress of water and dust and validated with IP protection class IP55.

You can now replace your conventional vehicle lamps with OSRAM's revolutionary NIGHT BREAKER LED retrofit lamps and experience trend-setting brightness for the first time with ECE-road approval.

Additionally, OSRAM offers a dedicated guarantee $^{3)}$ on all NIGHT BREAKER LED retrofit lamps.

Technical data

	Product in	formation							
Product description	Application (Category and Product specific)		Product legal advice 1		Product legal advice 2		e Pro	Product legal advice 3	
NIGHT BREAKER SMART H11 ECE LED	High beam, low beam and fog light		1) Homologated in accordance with the applicable UN ECE R37 regulations		2) Compared to the minimum requirements of ECE R112, while the glare is below the maximum permissible values by up to 50%		tra E lan are	n comparison to ditional Halogen nps	
			General P		Electrical Date	ta			
Product description	Product legal advice 4		Global order reference		Nominal wattage		No	Nominal voltage	
NIGHT BREAKER SMART H11 ECE LED	conditions refer to:	www.osram.com/am-				12	V		
		Photometr		ic Data				hysical Attributes & imensions	
Product description	Test voltage	Light color LED	t color Nominal luminous Lumino flux flux toleran			Length			
NIGHT BREAKER SMART H11 ECE LED	13.2 V	Cool white	1350	lm	±10 %		68.0 mi	n	
			Lifetime Data		Capabilities	Capabilities Certificate		standards	
Product description	Product we	Product weight		Lifespan B3	Technology	ECE Standards category		Standards	
NIGHT BREAKER SMART H11 ECE LED	BREAKER SMART H11 ECE 102.00 g		3000 hr	1500 hr	LED			ECE R37	
		ntal & Regulantal & Regulantal & Regulantal & Regulantal & Regular & Regulantal & Regular & Regu	•		(EC) 1907/200	6 (REA	(Ch)		
Product description	Primary article identifier		Candidate list substance 1		CAS No. of substance		ce Sat	e use instruction	
NIGHT BREAKER SMART H11 ECE LED	40621724	18331	Lead		7439-92-1		the sub suf saf	e identification of Candidate List ostance is ficient to allow e use of the icle.	

Product description	Declaration no. in SCIP database
NIGHT BREAKER SMART H11 ECE	b33327f1-2527-
LED	400e-ae81-
	f7f71177fc2c

Download Data

User instruction NIGHT BREAKER LED SMART ECE User instruction GPRS_Safety symbols instructions Brochures Night Breaker LED SMART ECE H11 Specification list Installation instruction (EN)

Safety advice

Application advice:

For more detailed application information and graphics please see the product datasheet, user manual and specification list

Legal advice

- 1) Homologated in accordance with the applicable UN ECE R37 regulations
- 2) Compared to the minimum requirements of ECE R112, while the glare is below the maximum permissible values by up to 50%
- 3) In comparison to traditional Halogen lamps
- 4) For precise conditions please refer to: www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.