

PrevaLED Linear TW G2

Modules linéaires



Caractéristiques produit

- Module efficacy: up to 170 lm/W with 2,700K
- Module efficacy: up to 190 lm/W with 6,500K
- Available module length: 62 mm, 280 mm, 560 mm
- Available with luminous flux: 245 lm, 1,100 lm and 2,200 lm
- Homogénéité initiale des couleurs : ≤ 3 SDCM
- Average lifetime (L80 B50): up to 70,000 h (temperature at $T_c = 55^\circ\text{C}$)

Avantages produits

- SELV or non-isolated LED Module with perfect match to Optotronic TW driver

Domaines d'application

- Bureaux
- Education

Fiche de données gamme de produits

Conseil d'application

Pour plus d'informations sur les applications et les graphiques, veuillez vous référer à la fiche de données produit.

Support de vente et support technique

Support de vente et support technique www.osram.fr

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Avertissement

Sous réserve de modifications. Sauf erreur ou omission. Veuillez à toujours utiliser la version la plus récente.