

ICUTRONICS FIT CS Track

Compact à courant constant - Non gradable



Caractéristiques produit

- AC Supply Voltage 220-240 Vac
- Fréquence de ligne : 50 Hz | 60 Hz
- Tension de ligne : 198 à 264 V,
- SELV LED driver in track adaptor
- Lifetime 50 000 h at tc max
- Dip-switches for easy output current selection
- Low THD <10% @ full load
- Low LF-ripple < 5%

Avantages produits

- Compact size for miniaturized track light luminaire design
- High light quality due to low ripple current
- Three colors available: White, Grey, Black

Domaines d'application

- Shops
- Commerces de détail
- Bâtiments publics
- Convient aux luminaires de classe de protection II
- Suitable for three circuits system

Fiche de données gamme de produits

Conseil d'application

Pour plus d'informations sur les applications et les graphiques, veuillez vous référer à la fiche de données produit.

Texte de la feuille de

- Hot plug-in or secondary switching of LEDs is not permitted and may cause a very high current to the LEDs.
 - Indication that the lamp control gear relies upon the luminaire enclosure for protection against accidental contact with live parts.
 - The max. mechanical loading F_{max} for the track driver mounted on the ceiling is 50N, which should be intended as the whole system inclusive of the weight of luminaires and accessories.
 - The max. mechanical loading F_{max} for the track driver mounted on the wall is 25N, which should be intended as the whole system inclusive of the weight of luminaires and accessories.
-

Support de vente et support technique

Support de vente et support technique www.osram.fr

Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Avertissement

Sous réserve de modifications. Sauf erreur ou omission. Veuillez à toujours utiliser la version la plus récente.