

LEDriving SL P21/5W WHITE

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Cool White



Replaces conventional P21/5W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P21/5W

LEDriving SL P21/5W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional P21/5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

	Product information			General Product Information		Electrical Data	
Product description	Application (Category and Product specific)	Product type (off- road vs. on-road)		Global order reference		Nominal voltage	
LEDriving SL ≙ P21/5W	Mainly used for signal/indicator applications	Off-road ≙ P21/5W	7528DWP		2.50 / 12 V 0.5 W		
			Photometric Data			Physical Attributes & Dimensions	
Product description	Nominal wattage	Test voltage	flux		Luminous flux tolerance	Diameter	
LEDriving SL ≙ P21/5W	1 W	13.5 V	145/30 lm		±15 %	27.0 mm	
		Lifetime Data		Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Product description	Diameter		Lifespan Tc			icle	

Product description	Candidate list substance 1	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
LEDriving SL ≜ P21/5W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	026eb835-3aa5- 4bfa-a635- bb4b42c468ab

1500 hr

27.0 mm

LED 1)

4062172151726 | 4062172401197

4000 hr

¹⁾ Light-emitting diode lamp

Product family datasheet

Download Data

File



User instruction
GPRS_Safety symbols instructions



Brochures

LEDriving Retrofits - Exchange overview (EN)

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.