

LEDDriving SL P21/5W RED

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Red




Replaces conventional P21/5W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P21/5W

LEDDriving SL P21/5W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional P21/5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

Product description	Product information		General Product Information	Electrical Data	
	Product type (off-road vs. on-road)	Application (Category and Product specific)	Global order reference	Power input	Nominal voltage
LEDDriving SL \triangleq P21/5W	Off-road \triangleq P21/5W	Mainly used for signal/ indicator applications	7528DRP	1.61 / 0.575 W	12 V

Product description	Nominal wattage	Power input tolerance	Test voltage	Photometric Data	Physical Attributes & Dimensions
				Nominal luminous flux	Lamp base
LEDDriving SL \triangleq P21/5W	1 W	$\pm 25\%$	13.5 V	100/10 lm	BAY15d

Product description	Length	Diameter	Diameter	Lifetime Data	
				Lifespan B3	Lifespan Tc
LEDDriving SL \triangleq P21/5W	52.5 mm	27.0 mm	27.0 mm	1500 hr	4000 hr

Product description	Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
	Technology	Primary article identifier	Candidate list substance 1	CAS No. of substance 1
LEDDriving SL \triangleq P21/5W	LED ¹⁾	4062172401319 4062172151740	Lead	7439-92-1

Product description	Safe use instruction	Declaration no. in SCIP database
LEDDriving SL \triangleq P21/5W	The identification of the Candidate List substance is sufficient to allow safe use of the article.	c811f6b4-522c-4ae4-b05c-1a7c56bdb77d

¹⁾ Light-emitting diode lamp

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.