Product family datasheet

LEDriving SL P27/7W RED

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications Available in Red




Easy upgrade to LED technology with plug & play solutions

Replaces conventional P27/7W lamps



Reliable OSRAM quality stands for less lamp replacements 4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P27/7W

LEDriving SL P27/7W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional P27/7W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| | Product informat | Product information | | General Product Information | | Electrical Data | | |
|------------------------------|--|--|---------------------------------|--------------------------------|---------------------------|-------------------------|-------------------|--|
| Product description | Application (Cate and Product spee | | | Global order reference | | Nominal voltage | | |
| LEDriving SL ≙ P27/7W | Mainly used for signal/ indicator applications | Off-road ≓ P27/7W | ≌ 3157DR | Ρ | 1.8 W | 12 V | | |
| | | | | Photometric | Data | Physical A Dimensior | ttributes & 1s | |
| Product description | Nominal wattage | e Power input toleranc e | Test voltage | Nominal luminous flux | | Lamp base | 2 | |
| LEDriving SL \doteq P27/7W | 1 W | ±25 % | 13.5 V | 60/10 lm | | W2.5x16q | | |
| | | | | | | Lifetime Data | | |
| Product description | Length | Diameter | | Diameter | | Lifespan B3 | Lifespan Tc | |
| LEDriving SL \doteq P27/7W | 49.0 mm | 25.7 mm | | 25.7 mm | | 1500 hr | 4000 hr | |
| | | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | | | | | |
| Product description | | Primary article dentifier | e Candidate list substance 1 | | CAS No. of substance 1 | | | |
| LEDriving SL ≙ P27/7W | LED ¹⁾ | 4062172151689 | Lead | Lead 7439-92-1 | | | | |

| Product description | Safe use instruction | Declaration no. in SCIP database |
|----------------------------------|---|--|
| LEDriving SL \triangleq P27/7W | The identification of the Candidate List substance is sufficient to allow safe use of the article. | a5c512b0-7fa2- 4907-bc1f- 816fe7f2d8ed |

4062172401777

 $^{1)}$ Light-emitting diode lamp

Product family datasheet

Download Data

| File |
|---|
| User instruction GPRS_Safety symbols instructions |
| Brochures LEDriving Retrofits - Exchange overview (EN) |

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.