Product family datasheet

LEDriving SL PS19W

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications Available in Cool White



Replaces conventional PS19W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements 4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for PS19W

LEDriving SL PS19W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional PS19W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| | Product infor | Product information | | General Product Information | | Electrical Data | | |
|---------------------------------|---|--|-----------------|------------------------------------|-------|-------------------------|-------------------|--|
| Product description | Product type (off- road vs. on-road) | Application (Catego and Product specifi | - | Global order reference | | Nominal voltage | | |
| LEDriving SL \triangleq PS19W | Off-road ≙ PS19W | Mainly used for daytime running lig applications | 5201DV Jht | VΡ | 1.8 W | 12 V | | |
| | | | | Photometric | Data | Physical A Dimensior | ttributes & ns | |
| Product description | Nominal watt | age Power input toleranc e | Test voltage | Nominal luminous flux | | Lamp base | e | |
| LEDriving SL \triangleq PS19W | 1 W | ±10 % | 13.5 V | 140 lm | | PG20-1 | | |
| | | | | | | Lifetime D | Jata | |
| Product description | Length | Diameter | | Diameter | | Lifespan B3 | Lifespan Tc | |
| LEDriving SL \triangleq PS19W | 42.5 mm | 15.5 mm | | 15.5 mm | | 1500 hr | 4000 hr | |
| | Capabilities | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | | | | | |
| Product description | Technology | Primary article identifier | | Candidate list C/ substance 1 1 | | No. of substance | | |
| LEDriving SL \triangleq PS19W | LED ¹⁾ | 4062172150293 4062172401456 | Lead | Lead 7439-9 | | 92-1 | | |

| Product description | Safe use instruction | Declaration no. in SCIP database |
|-----------------------------|-----------------------|-------------------------------------|
| LEDriving SL \doteq PS19W | The identification of | 6868705b-a925- |
| | the Candidate List | 4a87-a27f- |
| | substance is | 369be63e9f5a |
| | sufficient to allow | 11589200-5e74- |
| | safe use of the | 464c-a970- |
| | article. | 2b1ae6f9e2dc |

 $^{1)}$ Light-emitting diode lamp

Product family datasheet

Download Data

| File |
|---|
| User instruction GPRS_Safety symbols instructions |
| Brochures LEDriving Retrofits - Exchange overview (EN) |

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.