# **OSRAM**

## **BATTERYstart 300**

Jump starters



### **Engine size compatibility**

To jump start 12 V vehicles with up to 6 L petrol engines and 3 L diesel engines



#### **Battery Power**

Powerful 13,000 mAh Lithium Cobalt battery



#### **Powerbank-Function**

Charging electronic devices including smart phones and tablets



## Compact and powerful lithium jump starter with power bank feature

The OSRAM BATTERYstart300 compact Lithium Cobalt LiCoO2 jump starter for small to medium 12V vehicles up to 6L petrol engines and 3L diesel engines.

Smaller in size than most typical jump starters, the BATTERYstart300 is a compact solution without compromising on power. It includes intelligent safety clamps to keep the jump starter, user and vehicle safe with reverse-polarity, anti-spike and short circuit protection.

Comes with a bright LED light and a power bank feature, which allows you to charge electronic devices on the go – just connect a USB charger and the power bank will kick in.

## Product family datasheet

## Technical data

|                     | 1   |                             |  |   |
|---------------------|---|-----------------------------|--|---|
|                     | Product information                         |                             |  |   |
| Product description | Application (Category and Product specific) | Efficiency                  | Recommended Petrol<br>Engine size (up to)  | Recommended Diesel<br>Engine size (up to) |
| BATTERY start 300   | Lithium Starter                             | Better                      | 6 l  | 3 L                                       |
|                     |   |                             | General Product<br>Information   | Physical Attributes & Dimensions          |
| Product description | USB sockets 2.1A                            | 12V Power socket connection | Global order reference   | Length                                    |
| BATTERY start 300   | 2   | n/a                         | OBSL300  | 168.0 mm                                  |
|                     |   |                             | Environmental & Regulatory Information<br>Information according Art. 33 of EU<br>Regulation (EC) 1907/2006 (REACh) |   |
| Product description | Width                                       | Height                      | Candidate list substance 1   | CAS No. of substance                      |
| BATTERY start 300   | 88.0 mm                                     | 33.0 mm                     | Lead   | 7439-92-1                                 |

| Safe use instruction  | Declaration no. in  |
|-----------------------|---|
|                       | SCIP database   |
| The identification of | ada11f03-1c52-4c49-   |
| the Candidate List    | 9f3f-4ab9687039c7   |
| substance is          |   |
| sufficient to allow   |   |
| safe use of the       |   |
| article.              |   |
|                       | The identification of<br>the Candidate List<br>substance is<br>sufficient to allow<br>safe use of the |

## Product family datasheet

### Download Data

|   | File  |
|---|---|
| 大 | User instruction<br>BATTERYstart                        |
| • | Movie application<br>BatteryStart How to Video (ITA)    |
| D | Movie application BatteryStart How to Video (EN)        |
| • | Product movie OSRAM BATTERYstart 300 Product Video (EN) |

## Legal advice

Application advice:

For more detailed application information and graphics please see product datasheet.

## **Application advice**

For more detailed application information and graphics please see product datasheet.

### **Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.