

## LF3000 -G3-940-03 L1

LINEARlight FLEX High Power IP00 | Modules LED pour des applications professionnelles et industrielles



### Caractéristiques produit

- Bande de LED flexible et sécable

### Avantages produits

- Color uniformity better than 2 SDCM on the entire LED strip and between strips
- Grande sélection de teintes de couleur
- Montage facile sur de nombreuses surfaces lisses grâce à une bande autocollante située au dos

### Domaines d'application

- Éclairage de voûtes
- Intégration dans plafond



Fiche technique

Données électriques

|                                                   |                     |
|---------------------------------------------------|---------------------|
| Tension nominale                                  | 240 V               |
| Type de courant                                   | Courant direct (DC) |
| Puissance nominale par mètre                      | 25 W                |
| Puissance nominale                                | 7500 W              |
| Plage de tension                                  | 23...25 V           |
| Accidental reverse input voltage protection up to | 25 V                |

Données photométriques

|                                         |                     |
|-----------------------------------------|---------------------|
| Ra Indice de rendu des couleurs         | >90                 |
| Flux lumineux par mètre                 | 3100 lm             |
| Total des flux lumineux utiles          | 9300 lm             |
| Efficacité lumineuse                    | 124 lm/W            |
| Ecart-type de correspondance de couleur | ≤3 sdc <sub>m</sub> |
| Teinte de couleur (désignation)         | 4000 K              |
| Temp. de couleur                        | 4000 K              |

Données photométriques

|                              |          |
|------------------------------|----------|
| LED pitch                    | 14.29 mm |
| Angle de rayonnement         | 120 °    |
| Temps d'amorçage             | < 05 s   |
| Temps de préchauffage (60 %) | < 050 s  |

Information module de LED

|                             |    |
|-----------------------------|----|
| Nombre de LED par mètre     | 70 |
| Nombre de LED par composant | 7  |

Dimensions & poids



|                              |                      |
|------------------------------|----------------------|
| Longueur                     | 30000 mm             |
| Longueur – composant seul    | 100,0 mm             |
| Longueur de câble            | 5000                 |
| Poids du produit             | 4600 g               |
| Section du câble au primaire | 0.51 mm <sup>2</sup> |
| Largeur                      | 800 mm               |
| Hauteur                      | 140 mm               |

Température

|                                          |                            |
|------------------------------------------|----------------------------|
| T° fonctionnement confit norme IEC 62717 | 60 °C                      |
| Plage de température au point Tc         | -20...90 °C <sup>1)</sup>  |
| Plage de température ambiante            | -20...+50 °C <sup>2)</sup> |
| Plage de température de stockage         | -40...80 °C                |

<sup>1)</sup> Exceeding the maximum ratings will reduce expected life time or destroy the LED strip.  
<sup>2)</sup> Rated ambient temp. 25°C/Providing that temperature at Tc point is below max value during operation/Temperature ramping for environmental testing acc. to IEC 62717, 1K/min

Durée de vie

|                                      |         |
|--------------------------------------|---------|
| Durée de vie                         | 60000 h |
| Durée de vie nominale                | 60000 h |
| Flux résiduel en fin de vie nominale | 070     |
| Nombre de cycles de commutation      | 15000   |

Donnée produit supplémentaire

|                                     |                              |
|-------------------------------------|------------------------------|
| Code EAN de remplacement            | 4052899963962, 4062172143219 |
| ID of contained light source [AGGR] | LS_TRV_286600                |

Capacités

Fiche de données produit

|                       |       |
|-----------------------|-------|
| Lowest bending radius | 20 mm |
| Self-adhesive         | Oui   |
| With connection set   | Non   |
| With end piece        | Non   |

Certificats & Normes

|                                                       |                                                               |
|-------------------------------------------------------|---------------------------------------------------------------|
| Normes                                                | CE; ENEC 10 VDE/EAC/UL Recognized component according UL 8750 |
| Type de protection                                    | IP00                                                          |
| Energy efficiency class of the contained light source | E                                                             |

Données logistiques

|                        |             |
|------------------------|-------------|
| Nomenclature douanière | 85395100000 |
|------------------------|-------------|

Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |                                                                                                    |
|-----------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| Date of Declaration                                                   | 07-07-2023                                                                                         |
| Primary Article Identifier                                            | 4062172263894                                                                                      |
| Candidate List Substance 1                                            | Lead                                                                                               |
| CAS No. of substance 1                                                | 7439-92-1                                                                                          |
| Safe Use Instruction                                                  | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| Declaration No. in SCIP database                                      | 6578871f-23d4-4bf6-b5b3-f23e1a85fc02                                                               |

Technique / Accessoires

- Raccordement simplifié grâce au système d'appariement optionnel CONNECTsystem
- Installation rapide avec le système optionnel SLIM TRACK
- Parfaitement adapté aux ballasts électroniques OPTOTRONIC 24 V

Texte de la feuille de

- not relevant
- not relevant
- not relevant
- Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.

Données de téléchargement

|         |
|---------|
| Dossier |
|---------|

Fiche de données produit

|                                                                                     |                                                                       |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------|
|    | User instruction<br>LINEARlight FLEX POWER                            |
|    | Fiche technique produit<br>LINEARlight Flex Power Specification Sheet |
|    | Brochures<br>Light is freedom of design (EN)                          |
|    | Déclaration de Conformité<br>EAC Certificate                          |
|    | Déclaration de Conformité<br>UL Certificate                           |
|    | Déclaration de Conformité<br>ENEC10_VDE Certificate                   |
|    | Déclaration de Conformité<br>CB TEST CERTIFICATE DE1-57844            |
|    | Déclarations de conformité<br>LF HP G3 CE 4160937 280623              |
|    | Déclarations de conformité<br>LF HP G3 CE 3420012 03 071119           |
|    | Déclarations de conformité<br>EU Declaration of conformity            |
|   | Déclarations de conformité<br>Manufacturer declaration                |
|  | Eulmdat<br>LF3000-G3-940-03 L1 V2 LDT 28032022                        |
|  | IES data<br>LF3000-G3-940-03 L1 V2 IES 28032022                       |

Fiche de données produit

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Données logistiques

| Code produit  | Description produit  | Unité d'emballage<br>(Pièces/Unité) | Dimensions (longueur x<br>largeur x hauteur) | Volume               | Poids brut |
|---------------|----------------------|-------------------------------------|----------------------------------------------|----------------------|------------|
| 4062172263894 | LF3000 -G3-940-03 L1 | Carton de regroupement<br>8         | 241 mm x 195 mm x 205 mm                     | 9.63 dm <sup>3</sup> | 1301.00 g  |

Le code produit mentionné décrit la petite quantité d'unité qui peut être commandée. Une unité peut contenir un ou plusieurs produits. Lorsque vous passez la commande, merci de bien vouloir entrer une unité ou un multiple d'une unité.

Accessoires optionnels

| Description produit  | Nom de l'accessoire           | Code de<br>l'accessoire |
|----------------------|-------------------------------|-------------------------|
| LF3000 -G3-940-03 L1 | CONN-FLEX -2P-050 KIT 10PCS   | ▶ 4062172179591         |
| LF3000 -G3-940-03 L1 | CONN-FLEX -2P-200 KIT 10PCS   | ▶ 4062172179614         |
| LF3000 -G3-940-03 L1 | CORNER-FLEX -4P-003 KIT 10PCS | ▶ 4062172179638         |
| LF3000 -G3-940-03 L1 | CORNER-FLEX -4P-015 KIT 10PCS | ▶ 4062172179676         |
| LF3000 -G3-940-03 L1 | LTS-SLIMTRACK -2000 KIT 5 PCS | ▶ 4062172207300         |
| LF3000 -G3-940-03 L1 | FX-QMS-G1 -TU15H6W3-300       | ▶ 4052899448889         |
| LF3000 -G3-940-03 L1 | FX-QMS-G1 -TU16H12W3-300      | ▶ 4052899448988         |
| LF3000 -G3-940-03 L1 | FX-QMS-G1 -TU16H12-300        | ▶ 4052899448964         |
| LF3000 -G3-940-03 L1 | FX -SC08-G2-CT4PJ             | ▶ 4052899464858         |

Avertissement

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.