

OPTOTRONIC - 2DIM High Power IP67 AUX12

2DIM, AUX power, IP67 – constant current LED drivers



Domaines d'application

- Area lighting
- Stadium lighting
- Horticulture lighting
- Éclairage public et urbain
- Convient aux luminaires de classe de protection I

Avantages produits

- Easily programmable by OT Programmer-S; (AstroDIM / Constant lumen)
- Efficace et fiable
- 2DIM functionality in one device (AstroDIM, 1...10 V)
- Protection contre les surtensions : jusqu'à 10 kV
- Grande flexibilité grâce à une large plage de température de fonctionnement de -40 à 55 °C
- Lifetime: up to 100,000 h
- 5 years guarantee

Caractéristiques produit

- Disponible avec différentes puissances : 400 W, 600 W
- Tension d'alimentation : 220 à 240 V,
- AUX 12V output for sensor and wireless node
- Wide output current range
- Durée de vie: jusqu'à 100,000 h (at $T = 75\text{ °C}$ at T_c)

Fiche de données gamme de produits

Conseil d'application

Pour plus d'informations sur les applications et les graphiques, veuillez vous référer à la fiche de données produit.

Texte de la feuille de

- Input voltage range: Nominal operation at 198 – 264 Vac.
 - Output short circuit protection: shut down of driver occur in case of output short circuit without damage to the unit.
 - Output over load/voltage protection: In case the input voltage of the load exceeds the output voltage range which is auto defined by output current setting of the driver ($V_o = P_o / I_o$), it automatically reduces the output current. Auto-reversible without mains power on/off;
 - No load protection: the driver automatically adjusts the output voltage to the maximum output voltage which is auto defined by output current setting if no load is connected. Auto-reversible with the correct load connected;
 - Over temperature protection: the driver is protected against temporary overheating by shutting down until the overheating eliminated; Auto-reversible when temperature back to normal;
 - Disconnect the power before servicing. Terminal block is not included, installation must be performed by qualified person;
 - The protective earth (GNYE/PE wire, housing) has to be connected to the heat sink of the LED module to improve the capability of the system to withstand a surge and EMI in critical luminaires.
 - Not suitable to be mounted in ceiling corner
 - The LED control gear cannot be abutted against or covered by normally flammable materials or used in installations where building insulation or debris is, or may be, present in normal use.
 - The external flexible cable or cord of this driver cannot be replaced; if the cord is damaged, the driver shall be destroyed.
 - The dimmer should fulfill at least basic insulation between control voltage and dimming circuit (for Australia and New Zealand).
 - The startup time to reach the set output current is less than 2s.
 - For further details please consult the application note;
 - AUX 12V output for sensor and wireless node (max. 200 mA)
 - For output cable > 2m EMC conformity is not guaranteed and must be ensured by OEM
-

Support de vente et support technique

Support de vente et support technique www.osram.fr

Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Références/Liens

* For more information on the multi-level guarantee and the terms and conditions of the guarantee visit <https://>

Fiche de données gamme de produits

► www.inventronics-light.com/multilevel-guarantees

Avertissement

Sous réserve de modifications. Sauf erreur ou omission. Veuillez à toujours utiliser la version la plus récente.