

ELEMENT EM FIT SELV

Linéaire / Courant constant – Non gradable



Domaines d'application

- Éclairage de commerces
- Industry lighting

Avantages produits

- Boîtier à dimensions réduites
- Long lasting and high reliability
- High light quality due to low ripple current

Caractéristiques produit

- Fréquence de ligne : 50 Hz | 60 Hz
- Tension d'alimentation : 220 à 240 V,
- Wide output voltage range
- Fixed output (no dimming)

Fiche de données gamme de produits

Conseil d'application

Pour plus d'informations sur les applications et les graphiques, veuillez vous référer à la fiche de données produit.

Support de vente et support technique

Support de vente et support technique www.osram.fr

Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Avertissement

Sous réserve de modifications. Sauf erreur ou omission. Veuillez à toujours utiliser la version la plus récente.