

PrevaLED Linear OP

Modules linéaires



Caractéristiques produit

- Efficacité du module : jusqu'à 160 lm/W
- Color temperature: 3,000 K, 4,000 K or 6,500 K
- LED module in 14 mm width, 489 mm length, Luminous flux on: 800 lm
- LED module in 14 mm width, 1095 mm length, Luminous flux on: 1600 lm
- Homogénéité initiale des couleurs : ≤ 3 SDCM
- Average lifetime (L80 B50): $> 50,000$ h (temperature at $T_c = 75^\circ\text{C}$)
- CE, UKCA certified
- Indice de rendu des couleurs R_a : 80
- For indoor application

Avantages produits

- Design for slim and flat luminaire fixture
- Wide range of light colors
- High homogeneity thanks to LED optical lens

Domaines d'application

- Office
- Accueil
- Education
- Commerces
- Industrie

Fiche de données gamme de produits

Conseil d'application

Pour plus d'informations sur les applications et les graphiques, veuillez vous référer à la fiche de données produit.

Texte de la feuille de

- The LED module itself and all its components must not be stressed mechanically.
 - Installation of LED modules (with power supplies) needs to be made under consideration of all valid regulations and norms.
 - The modules are intended for operation only with matching OPTOTRONIC , ICUTRONIC and ELEMENT.
 - Pay attention to standard ESD precautions when installing the module.
 - Max. Voltage U-OUT = 60V for operation on SELV LED control gear.
 - The final luminaire assembled with modules must be well packaged with carton.
-

Support de vente et support technique

Support de vente et support technique www.osram.fr

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Références/Liens

* For more information on the multi-level guarantee and the terms and conditions of the guarantee visit [https://](https://www.inventronics-light.com/multilevel-guarantees)

▶ www.inventronics-light.com/multilevel-guarantees

Avertissement

Sous réserve de modifications. Sauf erreur ou omission. Veuillez à toujours utiliser la version la plus récente.
