

LEDriving HLM EASY H4/H19



Ultra compact LED replacement for conventional H4/H19 high and low beam lamps (2in1)

"Socket Design" – no adapters and caps needed



Easy plug & play installation



Cool White color temperature

Allowing a high compatibility and an easy installation.

Better visibility thanks to daylight effect



LED high and low beams lamps with plug & play system for motorcycles.

With its socket-based solution, the OSRAM LEDriving HLM EASY retrofits provide an ultra-compact LED replacement of conventional H4/H19 high and low beam lamps with cool white LED light - providing a stylish look as well as superior brightness. It offers an easy plug & play installation with optimized compatibility. An optimized high-speed fan ensures active cooling - making a higher performance and high-level light output possible thanks to maximized heat dissipation. The LEDriving HLM EASY high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a cool white color temperature. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for motorcycles with the respective halogen lamp types. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

	Electrical	Data	Photometric Data			
Product description	Power input	Nominal voltage	Nominal wa	attage	Nominal luminous flux	Luminous flux tolerance
LEDriving HLM EASY ≜ H4/H19	16.5W/1 6.5 W	12 V	19 W		1400/1100 lm	±25 %
	Physical A	Physical Attributes & Dimensions			Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Product description	Diameter	Diamete	er .	Lifespan Tc	Primary article identifier	
LEDriving HLM EASY ≜ H4/H19	21.5 mm	21.5 mn	1	1000 hr	4062172399821 4062172321525	

Product description	Candidate list substance 1	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
LEDriving HLM EASY ≜ H4/H19	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	b37dc721-98bb- 4626-9bd8- 5a2288767698 21ee7419-4eaf- 4d6d-96b9- 7d7968571c79

Product family datasheet

Download Data

File



User instruction

GPRS_Safety symbols instructions



Brochures

LEDriving Retrofits - Exchange overview (EN)

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.