Product family datasheet

LEDriving HLM EASY H7/H18



Ultra compact LED replacement for conventional H7/H18 high and low beam lamps (2in1) "Socket Design" – no adapters and caps needed



Easy plug & play installation

Allowing a high compatibility and an

easy installation.



OSRAM

Cool White color temperature of 6,000 K

Better visibility thanks to daylight effect



LED high and low beams lamps with plug & play system for motorcycles.

With its socket-based solution, the OSRAM LEDriving HLM EASY retrofits provide an ultra-compact LED replacement of conventional H7/H18 high and low beam lamps with cool white LED light - providing a stylish look as well as superior brightness. It offers an easy plug & play installation with optimized compatibility. An optimized high-speed fan ensures active cooling - making a higher performance and high-level light output possible thanks to maximized heat dissipation. The LEDriving HLM EASY high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a cool white color temperature. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for motorcycles with the respective halogen lamp types. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| | Electrical Data | | | Photometric Data | | |
|--|--|-----------------|------------|------------------|--|-------------------------------|
| Product description | Power input | Nominal voltage | Nominal wa | nttage | Nominal luminous flux | Luminous flux tolerance |
| LEDriving HLM EASY \triangleq H7/H18 | 16.0 W | 12 V | 16 W | | 1400 lm | ±25 % |
| | Physical Attributes & Dimensions Lifetin Data | | | Lifetime Data | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | |
| Product description | Diameter | Diamete | r | Lifespan Tc | Primary article identifier | |
| LEDriving HLM EASY ≙ H7/H18 | 20.0 mm | 20.0 mm | 1 | 1000 hr | 4062172399845 4062172321501 | |

| Product description | Candidate list substance 1 | CAS No. of substance 1 | Safe use instruction | Declaration no. in SCIP database |
|-----------------------------|-------------------------------|---------------------------|---|--|
| LEDriving HLM EASY ≙ H7/H18 | Lead | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | b8b846de-a024- 4936-a23c- b4a84c7f0784 c27fc65c-c089-4c9e- 8ffc-822db682f4c2 |

Product family datasheet

Download Data

 File

 User instruction

 GPRS_Safety symbols instructions

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.