


BoxLED M CP G5

Modules LED pour la publicité et la lumière rétro-éclairage



Caractéristiques produit

- Chaîne de 32 modules LED linéaires
- Relié avec des câbles flexibles
- Maximum length of one chain: 9.80 m
- Type de protection (modules) : IP66
- Dissipateur thermique entièrement intégré

Avantages produits

- Les modules sont compatibles avec le montage BackLED
- Éclairage uniforme grâce à des lentilles elliptiques optimisées
- Plusieurs options pour un montage simple et rapide : boulonnage ou encliquetage
- Excellente efficacité du module
- Lumière blanche uniforme (écart-type de correspondance de couleur SDCM: 3)
- Très longue durée de vie
- Garantie de 5 ans

Fiche de données gamme de produits

Technique / Accessoires

- Several types of OPTOTRONIC and ELEMENT 12 V power supplier
- BoxLED mounting profile BX-MP-M-CP-G5-2M
- BoxLED cable clip BX-CLIP-M-G5

Conseil d'application

Pour plus d'informations sur les applications et les graphiques, veuillez vous référer à la fiche de données produit.

Support de vente et support technique

Support de vente et support technique www.osram.fr

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Avertissement

Sous réserve de modifications. Sauf erreur ou omission. Veuillez à toujours utiliser la version la plus récente.