# **OSRAM**

# NIGHT BREAKER H1-LED

### OSRAM's first NIGHT BREAKER H1 LED



The NIGHT BREAKER LED family - OSRAM's first street-legal<sup>1)</sup> LED retrofit lamps.



#### 6000K & Cool White

See and be seen with OSRAM. Cool white color temperature similar to daylight. For more safety on the road, especially when driving at night



# Up to 5 times longer lifetime 3)

Vibration resistant, environmentally friendly, and cost-efficient



## 4 year OSRAM guarantee

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.



# With the NIGHT BREAKER H1 LED OSRAM's first street legal H1-LED replacement lamp is now on the market

With the street-legal 1) NIGHT BREAKER H1-LED you can now upgrade the function of your high- and low beam lights of your vehicle to state-of-the-art LED technology. These LED replacement lamps are suitable as a replacement for conventional H1 lamps and bases. They offer a modern and bright white light with a color temperature of up to 6000 Kelvin and impress with reduced glare for other road users that is up to 40% lower as the permissible maximum values<sup>2)</sup>. In comparison to standard lamps, such as halogen lamps, these LED retrofit lamps consume up to 55% less energy and convince thanks to the LED technology and the specially developed vibration-resistant design, with up to 5 times longer life time<sup>3)</sup>. You can now replace your vehicle lamps with OSRAM's revolutionary NIGHT BREAKER LED retrofit lamps and experience trend-setting brightness with road approval<sup>1)</sup> Additionally, OSRAM offers a dedicated guarantee on all NIGHT BREAKER LED retrofit lamps<sup>2)</sup>

# Product family datasheet

## Technical data

Product description	Product information  Application (Category and Product specific)	Product legal advi	ce Product l	egal advice	Product legal advice 3
NIGHT BREAKER H1 LED	High and low beam	1) Approved LED light source - only applies to the respective countri in which there is approval or to wh an equivalent approval applies the vehicle model and light function currently listed in compatibility list. more details see www.osram.com/rled	the mining requirement of the mining requirement of the maximum permissible and up to 40% of the for	ents of ECE ile the glare the n ole values by	3) Compared to halogen lamps
	General Product Information	Electrical Data			
Product description	Global order reference	Nominal voltage	Power input	Power input toleranc e	Nominal wattage
NIGHT BREAKER H1 LED	64150DWNB	12 V	16.0 W	±15 %	16 W
	Photometric Data				Physical Attribut es & Dimensi ons
Product description	Nominal luminous flux	Light color Co LED	olor temperature	Lumin flux tolera	base
NIGHT BREAKER H1 LED	1550 lm	Cool white 60	000 K	±15 %	P14.5s

Product description	Diameter	Diameter	Ī	Product weight	Length
NIGHT BREAKER H1 LED	11.8 mm	11.8 mm	50.00 g		76.2 mm
	Lifetime Data		Capabilities	Certificates & standards	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)
Product description	Lifespan Tc	Lifespan B3	Technology	Standards	Primary article identifier
NIGHT BREAKER H1 LED	2500 hr	1500 hr	LED	ABG	4062172373791

# Product family datasheet

Product description	Candidate list substance 1	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
NIGHT BREAKER H1 LED	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	903e3f51-c32d-4f87- bae4-4b7e9340d530

# Product family datasheet

#### **Download Data**

	File
<u> </u>	User instruction NIGHT BREAKER LED H1 64150DWNB
太	User instruction GPRS_Safety symbols instructions
乙	Brochures LEDriving Retrofits - Exchange overview (EN)

### Safety advice

Application advice: For more detailed application information and graphics please see product datasheet and user manual.

#### Legal advice

- 1) Approved LED light source only applies to the respective countries in which there is approval or to which an equivalent approval applies and the vehicle models and light functions currently listed in the compatibility list. For more details see www.osram.com/nb-led
- 2) Compared to the minimum requirements of ECE R112, while the glare is below the maximum permissible values by up to 40%
- 3) In comparison to traditional Halogen lamps
- 4) For precise conditions please refer to: www.osram.com/am-guarantee

## **Application advice**

For more detailed application information and graphics please see product datasheet.

## **Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

